

MFR-6100 Datasheet

1. Specifications

Basic specifications

Temperature / Humidity	0°C to 40°C / 30% to 85% (no condensation)
Power	100 VAC to 240 VAC \pm 10%, 50/60Hz IN
Consumption	SDI 144 x 144, Dual CPU/Redundant Power Unit (Maximum Configuration) 100 V AC to 120 V AC: 1500 VA (1500 W) 220 V AC to 240 V AC: 1584 VA (1457 W)
Dimensions	430 (W) x 576 (H) x 400 (D) mm, EIA 13 RU 480 (W) (Including rack mount brackets)
Weight	88.8 kg (Including all options)
Consumables	Power supply unit: Replace every 5 years FAN1-4 (P-1649): Replace every 4 years. FAN5-6 (P-1648): Replace every 4 years.

Technical specifications

Video Formats	
UHD 4K (12G-SDI)	2160/59.94p, 50p (SMPTE ST 2082-1)
(6G-SDI)	2160/30p, 29.97p, 25p, 24p, 23.98p (SMPTE ST 2081-1)
HD (3G-SDI)	1080/60p, 59.94p, 50p (SMPTE424M)
HD (HD-SDI)	1080/60i, 59.94i, 50i, 30p, 30PsF, 29.97p, 29.97PsF, 23.98p, 23.98PsF, 25p, 25PsF, 24PsF, 24p, 720/60p, 59.94p, 50p (SMPTE292M)
SD (SD-SDI)	525/59.94i, 625/50i (SMPTE259M)
Matrix Size	Min. 9 x 9 to Max. 144 x 144 (Expandable on a 9-channel basis) Number of input slots: 16 Number of output slots: 16
Video Input	
MFR-9SDI12GA	12G/6G/3G/HD/SD-SDI Input Card (16 cards Max.) 75-ohm BNC x 9
MFR-9SDI	6G/3G/HD/SD-SDI Input Card (16 cards Max.) 75-ohm BNC x 9
Video Output	
MFR-9SDO12GA	12G/6G/3G/HD/SD-SDI Output Card (16 cards Max.) 75-ohm BNC x 9 (Auto reclocking)
MFR-9SDO	6G/3G/HD/SD-SDI Output Card (16 cards Max.) 75-ohm BNC x 9 (Auto reclocking)

Process Delay	<p>When MFR-9SDI12GA and MFR-9SDO12GA cards are installed.</p> <p>12G-SDI: Less than 1.0 μs 6G-SDI: Less than 1.0 μs 3G-SDI: Less than 1.0 μs HD-SDI: Less than 1.5 μs SD-SDI: Less than 3.0 μs</p> <p>When MFR-9SDI and MFR-9SDO12GA cards are installed. When MFR-9SDI12GA and MFR-9SDO cards are installed.</p> <p>6G-SDI: Less than 0.5 μs 3G-SDI: Less than 0.5 μs HD-SDI: Less than 0.8 μs SD-SDI: Less than 1.5 μs</p>
Reference Input	BB: 0.429 Vp-p (NTSC) / 0.45 Vp-p (PAL) or Tri-level Sync: 0.6 Vp-p 75-ohm BNC x 2, loop-through (Terminate with 75-ohm terminator, if unused.)
Interfaces	
MFR-LAN	10/100 BASE-TX, RJ-45 x 2 (For connecting up to 128 RU/GPI units.) (Second LAN port used in redundant CPU configuration)
PC-LAN	10/100/1000 BASE-T, RJ-45 x 2 (for PC operation) (Second LAN port used in redundant CPU configuration)
SERIAL	RS-232C/RS-422 (Selectable), 9-pin D-sub (male) x 1
ALARM	9-pin D-sub 9 (female) x1 (Output: Power, Fan Alarm, Crosspoint Error, CPU changeover, Secondary CPU Error, MTX Alarm)

Options

MFR-61CPU	Redundant CPU card
MFR-61PS	Redundant power supply unit (AC cord retainer clip included.)
MFR-8RUA/18RUA/39RUA/40RU MFR-16RU/16RUD/16RUTA MFR-16RUW/32RUW/64RUW	Remote Control Unit

Accessories

AC cord and Quick setup guide

2. External Dimensions

(All dimensions in mm.)

