

## USF-204ADAC Datasheet

### 1. Specifications

#### Basic specifications

Temperature	0°C to 40°C
Humidity	30% to 90% (no condensation)
Power	+12 V DC (supplied by USF frame)
Consumption	Approx. 830 mA (+12V)
Dimensions	Front Module: 106 (W) x 356 (D) mm Rear Module: 114 (W) x 20.2 (H) mm
Weight	250 g
Required Slot	1 Slot

#### Technical specifications

Audio input	AES/EBU 1V (p-p) Unbalanced 75Ω BNC x 2 Stereo 2 channels 32/44.1/48 kHz
Audio output	Analog 4 channels Balanced or Unbalanced 25-pin D-sub, female x 1 100Ω and under, 24-bit
Maximum output level	+24 dBu
Frequency Characteristics	Within ±0.2 dB (20 Hz to 20 kHz, Standard: 1kHz)
Distortion ratio	0.05 % and fewer
S/N ratio	80 dB and more (A-Weighting)
Output level setting	-10 / 0 / +4 / +8 dBu
Gain adjustable range	-20.0 dB to +20.0 dB (in 0.1dB increments)
SNMP	Supports version v2c

#### Accessories

Screws for rear module installation and DVD-ROM

**2. External Dimensions**

(All dimensions in mm.)

