

Versatile delay

Solves audio/video delay issues



EDA-1000/2000

Video/Audio Delay Unit

3G/HD/SD-SDI 4-input audio/video delay that also support 4K. Choose from the compact EDA-1000 (1U half-size) or the EDA-2000 (1U), with a redundant power supply. Audio, video and VANC delay can be set separately.

Features

Delay of up to 80 sec. available (optional)

Using an HD-SDI input, set a delay of up to 40 sec. Add an EDA-20EX option for delay up to 80 sec. Set separate delays for each of the four inputs, as needed. For VANC data delay, minimum delay can be set per line for specific VANC within each input channel.

Available delay when four inputs are used is divided equally among channels (¼ the delay available for one channel).

Video Formats		Delay(Max.)			
		Standard		with EDA-20EX	
		1line	4 line	1line	4 line
3G-SDI	1920 x 1080/59.94p, 1920 x 1080/50p	20 sec	5 sec	40 sec	10 sec
HD-SDI	1920 x 1080/59.94i, 1920 x 1080/50i	40 sec	10 sec	80 sec	20 sec
SD-SDI	720 x 483/59.94i, 720 x 576/50i	120 sec	30 sec	240 sec	60 sec

Multi-format support

The units are 3G/HD/SD-SDI compatible. Delay both audio and video, or delay signals separately. They also supports 4K (Quad link 3G-SDI) input.

EDA-1000

Distribution is possible for up to four outputs when one channel of input is used. The unit is a compact 1U half-size model with a single power supply.

EDA-2000

Provides distribution of up to eight outputs when one channel of input is used. The EDA-2000 is a 1U model with redundant power supply.

Use SNMP for trap output or to check or configure settings

Remote control via Telnet with dedicated remote unit, the EDA-20RU


Genlock using external reference signals is enabled*

*Frame synchronization is not supported.

Specifications



Video inputs	3G-SDI: 1080/59.94p, 1080/50p, SMPTE ST 424 compliant HD-SDI: 1080/59.94i, 1080/50i, SMPTE ST 292-1 compliant SD-SDI: 720/59.94i, 720/50i, SMPTE ST 259 compliant
Video outputs	3G-SDI: 1080/59.94p, 1080/50p, SMPTE ST 424 compliant HD-SDI: 1080/59.94i, 1080/50i, SMPTE ST 292-1 compliant SD-SDI: 720/59.94i, 720/50i, SMPTE ST 259 compliant
	EDA-1000 75Ω BNC x 4 (4 lines, up to 4 distributed outputs when 1 line is used)
	EDA-2000 75Ω BNC x 8 (4 lines, up to 8 distributed outputs when 1 line is used)
Delay(Max.)	3G-SDI: approx. 20 sec. (40 sec.) HD-SDI: approx. 40 sec. (80 sec.) SD-SDI: approx. 120 sec.(240 sec.) *1/4 the delay available when 4 lines are used, 1/2 the delay available when 2 lines are used
Delay adjustment	VIDEO: Effective video section AUDIO: HANC space including audio signals VANC: VANC space
Reference input	BB: NTSC: 0.429 Vp-p/PAL: 0.45 Vp-p Tri-level sync: 0.6 Vp-p, 75Ω, BNC x 1 with loop-through
Phase adjustment	H Phase: ±0.5 Line, 1 Sample Step V Phase: ±0.5 Frame, 1 Line Step
LAN	100Base-TX, RJ-45 x 1 (remote control, SNMP v2c monitoring/control)
ALARM	15-pin D-sub (female), Fixed inch screw thread x 1 (Alarm output)
Alarm output	Power, FAN, Input signal fault detection, Genlock signal fault detection Output from SNMP-trap, ALARM connector
Temperature/Humidity	5°C to 40°C/10% to 80% (no condensation)
Power/Consumption	100 V AC to 240 V AC ±10%, 50/60 Hz/50 W (at 100 V AC)
Dimensions/Weight	EDA-1000 212 (W) x 44 (H) x 450 (D) mm/Approx. 5 kg
	EDA-2000 430 (W) x 44 (H) x 400 (D) mm/Approx. 6 kg
Consumables	Cooling fans (to be replaced every 5 years) Power unit (to be replaced every 3 years)
Accessories	AC cord, CD-ROM (Operation manuals, MIB files), Rack mount brackets (EDA-2000)
Options	EDA-20RU: Remote control unit EDA-20EX: Delay time extension

External View Diagrams





EDA-20RU

Unit: mm



EDA-1000



EDA-2000

FOR-A ELETEX FOR-A ELETEX Co., Ltd.

FOR-A COMPANY LIMITED

Head Office: 3-8-1 Ebisu, Shibuya-ku, Tokyo 150-0013, Japan

FOR-A Corporation of America Corporate Office: 11155 Knott Ave., Suite G&H, Cypress, CA 90630, USA

FOR-A Corporation of America Northeast Office: 2 Executive Drive, Suite 670, Fort Lee, NJ 07024, USA

FOR-A Corporation of America Southeast Office: 8333 North West 53rd Street, Suite 450, Doral, FL 33166, USA

FOR-A Corporation of America Service Center: 2400 N.E. Waldo Road, Gainesville, FL 32609, USA

FOR-A Europe S.r.l.: Via Volturmo, 37, 20861 Brugherio MB, Italy

FOR-A UK Limited: Trident Court, 1 Oakcroft Road, Chessington, KT9 1BD, United Kingdom

FOR-A Italia S.r.l.: Via Volturmo, 37, 20861, Brugherio MB, Italy

FOR-A Corporation of Korea: 1007, 57-5, Yangsan-ro, Yeongdeungpo-gu, Seoul 150-103, Korea

FOR-A China Limited: 1618 Huateng Building, No. 302, 3 District, Jinsong, Chaoyang, Beijing 100021, China

FOR-A Middle East-Africa Office: Dubai Media City, Aurora Tower, Office 1407, P.O. Box 502688, Dubai, UAE

AGIV (India) Private Limited: 2nd Floor, Valecha Chambers, Link Road, Andheri (W), Mumbai 400053, India

FOR-A South East Asia Office: Studio 09, Rm. A1, 3/F., Phase 1, Hang Fung Ind. Bldg., 2G Hok Yuen St., Hung Hom, Hong Kong

ISO 9001 and 14001 certified (Sakura R&D)

Design and specifications subject to change without notice.

www.for-a.com

Tel: +81 (0)3-3446-3936

Tel: +1-714-894-3311

Tel: +1-201-944-1120

Tel: +1-305-931-1700

Tel: +1-352-371-1505

Tel: +39 039-9164811

Tel: +44 (0)20-3044-2935

Tel: +39 039-881-086/103

Tel: +82 (0)2-2637-0761

Tel: +86 (0)10-8721-6023

Tel: +971 (0)4 551 5830

Tel: +91 22 2673 3623

Tel: +852-2110-9227