

USF-105DDA-12G Datasheet

1. Specifications

Basic specifications

Temperature	0 °C to 40 °C
Humidity	30% to 90% (no condensation)
Power	+12V DC (Supplied by USF frame)
Consumption	4.2VA (4.2W)
Dimensions	Front Module: 106 (W) x 357 (D) mm Rear Module: 114 (W) x 20.2 (H) mm
Weight	220 g
Required Slot	1 Slot

Technical specifications

Video Input	12G-SDI: 12Gbps 3G-SDI: 3Gbps HD-SDI: 1.5Gbps SD-SDI: 270Mbps DVB-ASI: 270Mbps 75Ω BNC x 1
Video Output	12G-SDI: 12Gbps 3G-SDI: 3Gbps HD-SDI: 1.5Gbps SD-SDI: 270Mbps DVB-ASI: 270Mbps 75Ω BNC x 5
Cable Compensation	Automatic Cable Compensation 12G-SDI: Max. 70m (L-5.5 CUHD-equivalent cable) 3G-SDI: Max. 100m (5C-FB-equivalent cable) HD-SDI: Max. 100m (5C-FB-equivalent cable) SD-SDI: Max. 200m (5C-2V-equivalent cable)
SNMP	Supports version v2c

Accessories

DVD-ROM and Screws for rear module installation

2. External Dimensions

(All dimensions in mm.)

